



NOTES

1. SCARIFY AND RECOMPACT THE UPPER 12" OF SUBGRADE TO 95% RELATIVE COMPACTION WITHIN THE LIMITS OF THE TRAILBED.
2. TRAIL SHALL HAVE A 5% MAXIMUM LONGITUDINAL GRADE.
3. REFERENCE GUIDE FOR THE DEVELOPMENT OF BICYCLE FACILITIES PREPARED BY THE AASHTO TASK FORCE ON GEOMETRIC DESIGN FOR DETAILS ABOUT HORIZONTAL ALIGNMENT, SIGHT DISTANCES, SIGNING AND MARKING, DRAINAGE, INTERSECTION, PAVEMENT STRUCTURE AND GRADE SEPARATION STRUCTURES.
4. 2' MINIMUM VEGETATION CLEARANCE ON EACH SIDE OF TRAIL. PRUNE ALL BRUSH OVER 12" HIGH AND 1/2" IN DIAMETER THAT EXTENDS INTO TRAILWAY.
5. CENTERLINE MARKING TO BE A 2" WIDE, CONTINUOUS YELLOW STRIPE.

CITY OF NAPA

PUBLIC WORKS DEPARTMENT

PAVED SURFACE SHARED TRAIL

DRAWN BY:	BRL	CHECKED BY:	DMP
DATE:	06/2018	APPROVED BY:	JRL
SCALE:	NONE	DRAWING NO.	PL-10
FIELD NOTES:			