



NOTES

1. SCARIFY AND RECOMPACT THE UPPER 12 INCHES OF SURFACE OR SUBGRADE TO 95% RELATIVE COMPACTION WITHIN THE LIMITS OF THE COMPACTED TRAILBED
2. TRAIL SHALL HAVE A 5% MAXIMUM LONGITUDINAL GRADE.
3. REFERENCE GUIDE FOR THE DEVELOPMENT OF BICYCLE FACILITIES PREPARED BY THE AASHTO TASK FORCE ON GEOMETRIC DESIGN FOR DETAILS ABOUT HORIZONTAL ALIGNMENT, SIGHT DISTANCES, SIGNING AND MARKING, DRAINAGE, INTERSECTIONS, PAVEMENT STRUCTURE, AND GRADE SEPARATION STRUCTURES.
4. 2' MINIMUM VEGETATION CLEARANCE ON EACH SIDE OF SHOULDER. PRUNE ALL BRUSH OVER 12" HIGH AND 1/2" IN DIAMETER THAT EXTENDS INTO TRAILWAY.
5. 2' MINIMUM SHOULDER OR CLEAR SPACE ON EACH SIDE OF TRAIL.

CITY OF NAPA

PARKS & RECREATION SERVICES DEPARTMENT

**DECOMPOSED GRANITE
SURFACE SHARED TRAIL**

DRAWN BY: SEO
 APPROVAL DATE: 05/2019
 SCALE: NONE
 REVISED DATE:

CHECKED BY: DMP
 APPROVED BY: JBL
 DRAWING NO. PL-11