



**SECTION A-A**

**NOTES:**

1. PLACE TRANSVERSE SCORE LINES AT 4' INTERVALS ON FACE OF CURB, RADIAL TO THE RADIUS POINT.
2. IN ADDITION TO THE REQUIREMENTS SHOWN ON THIS DRAWING, CURB RAMPS SHALL BE DESIGNED IN ACCORDANCE WITH THE CURRENT CALTRANS STANDARD A88A (SEE CITY STD. S-9).
3. WHERE EXISTING FACILITIES ARE NONCONFORMING OR RIGHT-OF-WAY LIMITATIONS EXIST, RAMPS MAY BE MODIFIED AS APPROVED BY THE CITY ENGINEER.
4. NEW CLASS II AB REQUIRED FOR ALL CONSTRUCTION.
5. ALL CONCRETE SHALL BE 4000 PSI (6 SACKS PER CUBIC YARD), 3/4" AGGREGATE.

CITY OF NAPA

PUBLIC WORKS DEPARTMENT

**STANDARD CURB RETURN -  
CURB, GUTTER, & SIDEWALK**

DRAWN BY:	LFM
APPROVAL DATE:	06/2018
SCALE:	NONE
REVISED DATE:	08/2021

CHECKED BY:	IHH
APPROVED BY:	JBL
DRAWING NO.	S-8